



Portable basketball system shall have a welded steel base with four 4" diameter non-marking casters for transport. Base shall require 425# of 4" x 8" x 16" solid concrete cap blocks for ballast inside an enclosed rear compartment. Rim height shall be adjustable from 6 1/2' to official 10' by means of telescoping square tubular members and an internal spring to assist in raising and lowering. All steel base components except the inner telescoping tube shall be powder coated silver grey. The inner telescoping tube shall be zinc plated. The backboard shall be 48" wide x 32" high 3/8" thick clear acrylic with an aluminum frame. The rim shall be a breakaway type and mounted through the backboard directly into the horizontal extension arm to eliminate stress on the backboard during play. The backboard shall be supported by supplemental bracing attached to the extension arm to increase backboard rigidity. A hinged lower front pad shall be designed to pull forward to allow transport and pushed closed for play. Front of base shall be padded with 1 1/2" foam covered with 14oz black vinyl. The distance from the face of the backboard to the front of the padding shall be 36" when the rim is at 10' and reduce to 28" when the rim is at 8'. Entire system shall weigh 450# without ballast and 875# with ballast. Warranty shall be 1 year.



## PRODUCT SPECIFICATION

BA833 Club Court Acrylic Basketball System

7/31/24 L.M.